





Design 3





FINISHES .XX

| STAINLESS STEEL | | | |
|-----------------|---|--|--|
| | I | | |
| | | | |

Satin Bright * .44 .43



STAINLESS STEEL POWDER COATED

STAINLESS STEEL POWDER COATED



COPPER PLATED WITHOUT COATING



Black burnished steel fixing screws Copper plated finish can vary significantly from batch to batch STAINLESS STEEL PVD GOLD



Satin .80

Black or white burnished steel fixing screws

| ART. | Α | В |
|------------------|--------------------------|-------------------------|
| GMP.D03.0005. xx | 127 mm 5 in | 58 mm 2 9/32" |
| GMP.D03.0006. xx | 152,4 mm 6 in | 58 mm 2 9/32" |
| GMP.D03.0007. xx | 177,8 mm 7 in | 58 mm 2 9/32" |
| GMP.D03.0008. xx | 203,2 mm 8 in | 58 mm 2 9/32" |
| GMP.D03.0009. xx | 228,6 mm 9 in | 58 mm 2 9/32" |
| GMP.D03.0010. xx | 254 mm 10 in | 58 mm 2 9/32" |
| GMP.D03.0011. xx | 279,4 mm 11 in | 58 mm 2 9/32" |
| GMP.D03.0012. xx | 304,8 mm 12 in | 58 mm 2 9/32" |
| | | |

* Stainless Steel Bright finish has a Satin inner profile

Hardwood or medium-density fiberboard (MDF) substrates are recommended when Design 2 and Design 3 pulls are used. Lesser grade materials, such as particle board, could affect connection strength.

Satin

.99